

Mixer Type:

## EKATO UNIMIX SRC

The models of the UNIMIX SRC series are the most frequently sold units in the complete range due to their versatility.

The general features are as follows:

- In line with cGMP requirements
- Hydraulic lid lifting device
- Vacuum/pressure tight
- Heating/cooling system
- PARAVISC (EKATO Patent) - agitator system with wall scrapers (other agitators are available)
- Patented homogenizer EKATO UNIMIX S-JET, at lowest point in vessel for internal/external homogenization
- Various control systems available
- Remote maintenance
- Open design, easy maintenance and inspection
- Scrapers can easily be exchanged
- Product residues can easily be scraped off when lid with agitator is in raised position
- ATEX/explosion proof design available



EKATO UNIMIX SRC 2000

All machines within this production range have special features assuring safe and economical production for a wide variety of products and viscosities.

The UNIMIX SRC – mixers are used worldwide and enjoy an excellent reputation for the production of ointments, gels, suspensions, toothpaste and skin care as well as a range of specialities within the food and chemical industry.

# EKATO SYSTEMS

EKATO SYSTEMS GmbH  
Käppelemattweg 2  
79650 Schopfheim  
Germany  
Tel. +49 (0) 7622 29-400  
Fax +49 (0) 7622 29-600  
E-mail: systems@ekato.com

www.ekato.com



EKATO UNIMIX SRC 1000

## EKATO UNIMIX SRC

Type	Volume (l)	Length (mm)	Width (mm)	Height lid closed (mm)	Lid lifting max. (mm)	Weight (kg)
SRC 100	100	1250	850	2160	700	740
SRC 150	150	1300	900	2280	810	780
SRC 200	200	1350	950	2420	890	890
SRC 250	250	1370	950	2480	940	1040
SRC 320	320	1420	980	2580	1030	1130
SRC 400	400	1450	1450	2740	1030	1440
SRC 500	500	1500	1500	2900	1130	1730
SRC 630	630	1570	1570	2960	1160	2060
SRC 800	800	1570	1570	3230	1390	2250
SRC 1000	1000	1630	1630	3530	1460	2760
SRC 1250	1250	1730	1730	3610	1520	3030
SRC 1600	1600	1850	1850	3770	1650	4040
SRC 2000	2000	1950	1950	3940	1750	4550
SRC 2500	2500	2100	2100	4470	1950	6270
SRC 3000	3000	2200	2200	4570	2030	7470
SRC 4000	4000	2450	2450	4700	2120	8750

Approximate dimensions